

PA3500EX ACCESSORIES



PA3500EX

Part No.	Description	mm	mm	mm	qty	qty
PA3500EX	High Performance .27 Caliber low Velocity Tool				1	n/a



8mm Drive Pin

Part No.	Description	mm	mm	mm	qty	qty
50016	5/8" (knurled) x 8mm head	8	3.7	16	100	5000
50182	3/4" (knurled) x 8mm head	8	3.7	19	100	5000
50022	3/4" x 8mm head	8	3.7	19	100	5000
50026	1" x 8mm head	8	3.7	25	100	5000
50032	1-1/4" x 8mm head	8	3.7	32	100	1000
50034	1-1/2" x 8mm head	8	3.7	38	100	1000
50036	1-3/4" x 8mm head	8	3.7	45	100	1000
50038	2" x 8mm head	8	3.7	50	100	1000
50040	2-1/4" x 8mm head	8	3.7	57	100	1000
50042	2-3/8" x 8mm head	8	3.7	60	100	1000
50044	2-1/2" x 8mm head	8	3.7	65	100	1000
50046	2-3/4" x 8mm head	8	3.7	70	100	1000
50048	3" x 8mm head	8	3.7	75	100	1000




8mm Ballistic point step drive pin for steel & hard concrete

Part No.	Description	mm	mm	mm	qty	qty
SC50038	50 x 8mm head	8	4	50	100	1000
SC50042	60 x 8mm head	8	4	60	100	1000
SC50048	75 x 8mm head	8	4	75	100	1000



8mm Drive Pin with Top Hat

Part No.	Description	mm	mm	mm	qty	qty
50138	5/8" (knurled) x 8mm head	8	3.7	16	100	5000
50140	3/4" x 8mm head	8	3.7	19	100	5000
50144	1" x 8mm head	8	3.7	25	100	5000



8mm Drive Pin Washered

with 7/8" (22mm) Washer. To provide resistance to pullover, these pins are available with preassembled 14 gauge (1.9mm) metal washers. Resistance to pullover is increased by the additional bearing surface provided by the washer.

Part No.	Description	mm	mm	mm	qty	qty
50090	1" x 8mm head	8	3.7	25	100	1000
50092	1-1/4" x 8mm head	8	3.7	32	100	1000
50094	1-1/2" x 8mm head	8	3.7	38	100	1000



8mm Drive Pin with Insulation Washer

with 1-7/16" (36mm) Insulation Washer (0.9mm thick)

Part No.	Description	mm	mm	mm	qty	qty
50122	1-1/2" x 8mm head	8	3.7	38	100	1000
50126	2-1/2" x 8mm head	8	3.7	65	50	500



8mm Washered Pin with Top Hat

with 7/8" (22mm) Washer

Part No.	Description	mm	mm	mm	qty	qty
DP820W	Washed Drive Pins 20mm w/ Top Hat	8	3.7	20	100	1000
DP825W	Washed Drive Pins 25mm w/ Top Hat	8	3.7	25	100	1000
DP830W	Washed Drive Pins 30mm w/ Top Hat	8	3.7	30	100	1000



8mm Pins with Ceiling Clip

Part No.	Description	mm	mm	mm	qty	qty
50368	1" x 8mm head	8	3.7	25	100	1000
50374	1-1/4" x 8mm head	8	3.7	32	100	1000



8mm Pins with Cable Tie

Part No.	Description	mm	mm	mm	qty	qty
50390	PA Cable Tie 240mm	8	3.7	32	n/a	500



8mm Pins with Conduit Clip Assembly

Part No.	Description	mm	mm	mm	qty	qty
50382*	1/2" EMT 1" pin x 8mm head	8	3.7	25	100	1000
50386*	3/4" EMT 1" pin x 8mm head	8	3.7	25	100	500
50388*	1" EMT 1" pin x 8mm head	8	3.7	25	25	250

* discontinued item once current stock exhausted



.27 Caliber Safety 10 Load Strip

to suit: Powers Tools PA3500, R3500, PA3500EX. Ramset Tools S75A, TS750, TS60P, FORM MASTER™, FIX MASTER™, TY MASTER™, FRAME MASTER™, TS750P, Reid Tools EXP360, BET0200, EXP75, EXP460 and Hilti Tools DX350, DX36M, DX450, DXA40, DXA41, DX351, DX460

Part No.	Description	Colour	qty	qty
50622	.27 cal Green Safety Strip	Green	100	1000
50626	.27 cal Yellow Safety Strip	Yellow	100	1000
50630	.27 cal Red Safety Strip	Red	100	1000



Pole Tool for PA3500 and PA3500EX and Accessories

Part No.	Description	qty	qty
PA3500-PT	Pole Tool for PA3500 and PA3500EX	1	n/a
ACCESSORIES			
52034	Tool Lubricant	1	n/a

71 TOPHAM RD SMEATON GRANGE NSW 2567

P: (02) 4647 4333 E: sales@ablefix.com.au
F: (02) 4647 7934 W: www.ablefix.com.au



PA3500EX

EXTRA HIGH POWERED

LOW VELOCITY
POWDER ACTUATED
FASTENING TOOL

.27
CALIBER
SEMI
AUTOMATIC

71 TOPHAM RD SMEATON GRANGE NSW 2567

P: (02) 4647 4333 E: sales@ablefix.com.au
F: (02) 4647 7934 W: www.ablefix.com.au

 **ABLE FIX**
FASTENERS

Extra High Powered, Low Velocity,

.27 CALIBER FASTENER

Ergonomic Rubber Handle Pad for high volume use

Power Adjust allows precise penetration of the pin through the fixture and into the base material.
1 = min. power 6 = max. power

The PA3500EX is a high quality, high powered, low velocity, semi automatic tool designed for high speed and repetitive volume applications, the tool features an automatic .27 caliber strip load advance system, an engineered plastic, heavy duty tool body and rubber handle pad to minimize the effects of recoil.

In order to drive the fastener into the base material, the tool operates using the indirect acting piston principle in which an internal drive piston impacts the fastener to drive it into the base material.

TECHNICAL DATA

Tool Length:	370mm
Tool Weight:	2.3kg
Pin Type:	7.6mm Head Drive Pin 8mm Head Drive Pin 1/4" -20 Threaded Stud
Pin Length:	13mm to 75mm
Load Type:	.27 Caliber in a 10 Load Strip
Power Level:	Green (3), Yellow (4), Red (5)

Powder Actuated FASTENING TOOL

.27
CALIBER
SEMI
AUTOMATIC



Fastener Guide



Engineered Plastic Housing provides durability and lightweight performance

Fully equipped tough and lockable carry case



NEW 8mm Ballistic point step shank drive pin for thick steel & hard concrete
Ideal for timber frame connection to concrete and steel