Sikabond® T55J

Version 1.0 SDS Number: 000000601639 Revision Date: 10.01.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikabond® T55J

Product code : 000000601639

Type of product : liquid

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Telefax : +61 2 9725 33 30

E-mail address : EHS@au.sika.com

Emergency telephone num-

ber

: +61 1800 033 111

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity - repeated expo-

sure (Inhalation)

: Category 2 (Central nervous system)

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H373 May cause damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention**:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

nent.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Sikabond® T55J



SDS Number: 000000601639 Revision Date: 10.01.2018 Version 1.0

alcohol-resistant foam for extinction.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

P314 Get medical advice/ attention if you feel unwell. P370 + P378 In case of fire: Use dry sand, dry chemical or

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes,	64742-82-1	>= 1 - < 10
cyclics, aromatics (2-25%)		
aromatic polyisocyanate	53317-61-6	0 -<1
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -<1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and : No known significant effects or hazards.

See Section 11 for more detailed information on health effects and symptoms.

delayed

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician : Treat symptomatically.

Sikabond® T55J

SDS Number: 000000601639 Revision Date: 10.01.2018 Version 1.0

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: Water

High volume water jet

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread

Hazardous combustion prod-

: No hazardous combustion products are known

Specific extinguishing meth-

ods

: Use water spray to cool unopened containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Use explosion-proof equipment. Keep away from

heat/sparks/open flames/hot surfaces. No smoking. Take pre-

cautionary measures against electrostatic discharges.

Do not breathe vapours or spray mist. Advice on safe handling

Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

Sikabond® T55J



Version 1.0 SDS Number: 000000601639 Revision Date: 10.01.2018

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further information: Sensitiser				
		STEL	0.07 mg/m3 (NCO)	AU OEL	
	Further information: Sensitiser				
		TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser				
		STEL	0.07 mg/m3 (NCO)	AU OEL	
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser				

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

Sikabond® T55J

Version 1.0 SDS Number: 000000601639 Revision Date: 10.01.2018

cific work-place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : light brown

Odour : ester-like

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : ca. 38 °C (100 °F)

Method: closed cup

Evaporation rate : No data available

Flammability : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.01 hPa (0.01 mmHg)

Relative vapour density : No data available

Density : ca. 1.37 g/cm3 (23 °C (73 °F) ())

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

Sikabond® T55J

Version 1.0 SDS Number: 000000601639 Revision Date: 10.01.2018



SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

aromatic polyisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Sikabond® T55J

Version 1.0 SDS Number: 000000601639 Revision Date: 10.01.2018

STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

Sikabond® T55J

Version 1.0 SDS Number: 000000601639 Revision Date: 10.01.2018

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements : There is no applicable prohibition or

notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory

legislation.

Not applicable

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Date format : dd.mm.yyyy

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.